



PART NUMBER	DESCRIPTION	DIMENSIONS	LUMENS PER FIXTURE	TOTAL WATTS PER FIXTURE	FINISH OPTIONS	KELVIN TEMP.
L-BL09-- <i>Finish</i> -TW	9" 120-volt Bar Light with 3 selectable white temperature options	9-1/2" x 3" x 1"	340	5	Black (BK) Dark Silver (DS) White (WT)	3000K/4000K/5000K/ Selectable
L-BL12-- <i>Finish</i> -TW	12" 120-volt Bar Light with 3 selectable white temperature options	11-7/8" x 3" x 1"	480	7	Black (BK) Dark Silver (DS) White (WT)	3000K/4000K/5000K/ Selectable
L-BL18-- <i>Finish</i> -TW	18" 120-volt Bar Light with 3 selectable white temperature options	17-7/8" x 3" x 1"	700	9.5	Black (BK) Dark Silver (DS) White (WT)	3000K/4000K/5000K/ Selectable
L-BL24-- <i>Finish</i> -TW	24" 120-volt Bar Light with 3 selectable white temperature options	23-15/16" x 3" x 1"	950	12	Black (BK) Dark Silver (DS) White (WT)	3000K/4000K/5000K/ Selectable
L-BL32-- <i>Finish</i> -TW	32" 120-volt Bar Light with 3 selectable white temperature options	31-15/16" x 3" x 1"	1300	16	Black (BK) Dark Silver (DS) White (WT)	3000K/4000K/5000K/ Selectable

Blue indicates choice selection. L-BL18-BK-TW (Example part number for 18" Bar Light, Black Finish)

FEATURES

- 3 White light temperature selectable via a switch on face, select between 3000K, 4000K, or 5000K
- No separate power supply needed
- Hardwired or Plug-in ready (cord sold separately)
- Linkable (end-to-end connector included; linking cable sold separately)
- 90+ CRI (Color Rendering Index – true color)
- Simple installation
- 5-year limited warranty
- Designed for indoor applications
- No UV or IR
- Dimmable (with compatible wall dimmer)
- Switch on device for high–medium–off light output
- 50,000 hour LED life at 70% lumen maintenance

APPLICATIONS

- Under cabinet
- Under shelf
- Office

TECHNICAL INFORMATION

Input Voltage	120-volt
Color Temperature (Kelvin)	Soft white 3000K Cool white 4000K Daylight white 5000K
CRI (Color Rendering Index)	90+
LED Type	2835 SMD
IP Rating	IP40
Dimmable	10% – 100%
Rating	ETL/FCC/CA Prop 65
Rated Life	50,000 hrs
LED Beam Angle	110°
LED Spacing	1/4"
Mounting	Screws (included)
Wiring	12–14 gauge solid (hardwired option) Plug-in cord (sold separately for plug-in option)
Operating Temperature	-4°F to 122°F (-20°C to 50°C)
Environment	Dry locations
Construction Material	Aluminum with acrylic lens
Warranty	5 years