

**Wardrobe lifts: Installation and Operating Tips** (REV 9/09)**Installation tips:****Install both Mounting Boxes in the same location on adjacent side panels:**

Please take special care to mount the Mounting Boxes in the same location (set-back and height) on each panel. This will avoid the lift from racking or binding allowing lift to perform correctly. See included Alignment Block which is used in conjunction with line holes to assure Mounting Boxes are installed at the same height.

Be sure the set-back of Mounting Boxes is accurately measured and is the same on both sides.

- Be sure to use all Mounting Screws to assure a strong attachment to side panels.
- Be sure to install Bumper Brackets on both sides.

**Adjustable Wardrobe rail needs to be locked:**

Once the Mounting Boxes are mounted to the side panels and the Adjustable Wardrobe Rail is extended to the proper width, twist the outer sleeves of the Adjustable Wardrobe Rail in opposite directions to **lock in the width**.

Over or under extending the width of the Wardrobe rail may create binding with the vertical arms. (See step 4 in the mounting instructions)

**Not locking the width may also cause the Wardrobe rail to bend or bow.**

**Bumper Brackets:**

Be certain Bumper Brackets are mounted on both sides before operating lift. Failure to do so will cause damage to the plastic Mounting Boxes. (See step 1 in the mounting instructions).

**Operating tips:**

**Cycle the lift.** Once the lift is installed, cycle the unit three to five times to loosen the pistons to allow for smooth operation.

**Handle pole needs to be located in the center of the Wardrobe rail and pulled straight down and not at an angle.** This will avoid binding and ensure proper operation of the lift. Pre-installed O-rings keep the T-Bracket in position.

**Assist the lift when lowering.** When lowering the lift, assist the Handle Pole until the vertical arms rest on the Housing Bumpers. Letting the lift drop on its own may cause damage to the housing.

**Distribution and Weight Limit:** Loading the lift with more weight than the weight limit will cause damage to the lift. Distribute weight of clothes evenly across the Wardrobe Rail to avoid “racking”.

---

**Load/weight Limit of the wardrobe lifts:**

26 lbs (12 kg) Item numbers	<b>Chrome</b>	<b>Black</b>
	805.31.201	805.31.301
	805.31.202	805.31.302
	805.31.203	805.31.303

**Operation tips:**

- 1) **Bumpers pre-installed on housings:** Do not remove pre-installed bumpers. The removal of one or both bumpers may cause damage to the housing during use.
  - 2) **Handle pole needs to be located in the center of the Wardrobe rail and pulled straight down and not at an angle:** This will avoid binding and ensure proper operation of the lift. Pre-installed O-rings keep the T-Bracket in position.
  - 3) **Assist the lift when lowering:** When lowering the lift, assist the Handle pole until the vertical arms rest on the Housing bumpers. Letting the lift drop on its own may cause damage to the housing.
  - 4) **Distribution and Weight Capacity:** Loading the lift with more weight than capacity will cause damage to the lift. Distribute weight of clothes evenly across the Wardrobe rail to avoid “racking”.
-