



Chimney

BWS2 SERIES

This sleek low-profile design is the perfect statement for today's kitchens. Available in stainless steel and black stainless-steel finishes. Bright LED lighting enhances your cooking experience, while the 3-speed backlit soft touch control makes operation easy.

SIZE	SIZE STAINLESS BLACK STAINLESS		GREASE FILTERS (replacement)	NON-DUCTED CHARCOAL FILTERS		
29-1/2 in.	BWS2304SS	BWS2304BLS	S9910487 (set of 2)	FILTERBWPTS (set of 2)		

HVI PERFORMANCE	HVI PERFORMANCE										
	Size	Damper	Sones			CFM					
Duct Orientation			Normal	Medium*	High	Normal	Medium*	High 0.25 in. w.g.	High 0.1 in. w.g.		
Round - Vertical	6 in.	Included	3.0	5.5	8.5	240	350	385	400		

FEATURES					
Max Blower Airflow	450 CFM				
Finish	430 Stainless Steel no. 4 Brushed				
Wall Mount	Yes				
Telescopic Flue	Yes - Accomodates 8-ft. to 9-ft. ceilings				
Convertible to non-ducted operation	Yes - Non-Duct Kit ARKBWS sold separately				
Blower type	Single, Centrifugal				
Cord-connected	Yes				
Control type	Soft-Touch Blower low speed Blower medium speed Blower high speed Light on-off 5-Minute delay				
Lighting	2 x LED Modules 5.5 W, (included)				
Grease Filters	Hybrid baffle filters, dishwasher-safe with quick-release latch				

AC INPUT

120 V, 60 Hz - 2.6 AMPS

	OPTIONAL ACCESSORIES (sold separately)								
Flue Extension for 10-ft. ceiling		AEBWS (stainless steel), AEBWSBLS (black stainless steel)							
	Non-Duct Kit	ARKBWS							
	Airflow Reducer	ARP6							

MOUNTING HEIGHT


26-in. from cooktop to bottom of hood

LIMITED WARRANTY

1-year (See installation manual for full warranty text.)

)F	RINDO	OOR	US	E ON	ILY						
3.	.0									Vortice	al High Spe	od
2.	.5		_	_						6-in. ro		eu,
Static pressure (in. w.g.)	.0					\	_					
ssure	.5											
and 1.	.0											
o.	.5											
	0	51	0	100	150	200	2	50	300	350	400	45
						Airf	low (cfn	n)				









HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 and 0.25 in. static pressure at high speed based on tests conducted in an HVI-approved state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

* Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.