



### Installation Requirements

The Floating Shelf Clamp System is a lightweight shelf system that includes a 6" deep shelf and an adjustable bracket. This system can be used on any wall and allows for a shelf thickness between 0.75"- 1.69". To start, install the metal C shaped bracket onto the wall using the flat head screws provided. Then, use the knurled thumbscrew to lock the shelf between the top face of the metal bracket and clamp. Make sure you use drywall anchors (if needed) and don't forget to level across each bracket.

Before beginning, you will need the following components:

- Drill with 3/16" Bit
- Flat Head Screwdriver or Drive Bit
- Bubble Level
- Dry Wall Anchors and Measuring Tape

### Floating Shelf Clamp System (FB-06839, FB-06840, FB-06842)

1. Determine the placement on the wall that you would like to install your Floating Shelf Clamp System
2. Install the bracket on the stud wall or drywall using the fastener provided. Feel free to use a stud finder for maximum support. Keep spacing less than 16" on the center and use your bubble level to make sure the brackets are even.



3. Then, lock the shelf between the top flange of the bracket and the clamp by using the fastener provided. Tighten the thumbscrew rotating clockwise.

4. Make sure it is level and tight enough for your convenience.

### Final Steps

Enjoy your work. We are happy that you chose to support your project with Federal Brace brackets. We would be very grateful for images of your finished installation. Everyone enjoys seeing Federal Brace supports at work. Also, know that the highest compliment Federal Brace can receive is a reference from our customers to their friends and family. If you have enjoyed your buying experience with Federal Brace, please let someone know. Thank you!