









EKU Porta 100 GFO

Item No.
941.00.007

Set Components

	Description	Material	Color/Finish	Qty.	Item No.
	Double roller running gear	-	-	2 pcs.	941.00.015
	Suspension bolt, M8 x 32	Steel	zinc-plated	2 pcs.	940.54.021
	Set nut, M8	Steel	zinc-plated	2 pcs.	940.54.022
	Clamp shoe adjustable from 6 - 12.7 (1/4" - 1/2")	Aluminum	mill finish	2 pcs.	941.00.020
	Track stopper, with adjustable retention spring	Plastic	gray	1 pc.	940.60.043
	Track stopper	Plastic	gray	1 pc.	940.60.041
	Floor guide, adjustable from 6 - 12.7 (1/4" - 1/2")	-	-	1 pc.	941.00.031
	Buffer	Rubber	black	1 pc.	940.60.051

Note

Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm
Inches are approximate

EKU Porta 100 GFO

Individual Components

	Description	Material	Color/Finish	Length	Item No.
	Wall brackets, set for mounting 1 upper track	-	-	-	941.00.060
	Upper tracks, pre-drilled, 95 X 62 (3 47/64" x 2 7/16")	Aluminum	unanodized	2.5 m (8' 2 7/16")	941.00.254
	Upper tracks, pre-drilled, 95 X 62 (3 47/64" x 2 7/16")			6 m (19' 8 1/4")	941.00.604
	Reinforcement profile, 43 X 70 (1 11/16" x 2 3/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.01.525
				6 m (19' 8 1/4")	941.01.560
	Clip-on fascia to upper track, 94.5 X 9 (3 23/32" x 23/64")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.00.825
				6 m (19' 8 1/4")	941.00.860
	Support profile for fixed glass, pre-drilled, 53 X 19 (2 3/32" x 3/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.01.825
				6 m (19' 8 1/4")	941.01.860
	Fixed glazing profile/lower guide channel, Pre-drilled, 30 x 20 (1 3/16" x 25/32")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.01.725
				6 m (19' 8 1/4")	941.01.760
	Angle profile for fixed glass, pre-drilled, 30 X 19 (1 3/16" x 3/4")	Aluminum	anodized	2 m (6' 6 3/4")	941.01.420
	Angle profile for fixed glass, 30 X 17 (1 3/16" x 11/16")	Aluminum	anodized	2 m (6' 6 3/4")	941.01.320
	Wall profile, 38 x 21 (1 1/2" x 59/64")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.24.925
				3.5 m (11' 5 13/16")	941.24.935
	Seal for wall profile	Rubber	black	2.5 m (8' 2 7/16")	941.24.081
				3.5 m (11' 5 13/16")	941.24.082
	Fixing set for support profile and Fixed glazing profile	-	-	-	941.01.899
	Sealing profile for 8 and 10 (5/16" and 3/8") glass	Rubber	black	20 m (65' 7 7/16")	941.00.103
	Seal	Plastic	black	20 m (65' 7 7/16")	941.00.094
	Soft closer 10 - 60 kg (22 - 132 lbs.)				940.60.045
	Soft closer 61 - 100 kg (135 - 220 lbs.)	-	-	-	940.60.010
	Cover cap for notched service access in track				940.60.094

Note

Mounting instructions (included in fitting set) for planning and execution available upon request.

Floor mounted door stop

page 1.206

HAWA Toplock

pages 1.283-1.287

Dimensions in mm
Inches are approximate

AH 1.214

kitchensource.com

1.800.667.8721